

DC-PTZ12-4K



DESCRIPTION:

DGX Digital's DC-PTZ12-4K Series is a high-performance 4K PTZ camera designed for professional applications. Featuring a 1/2.8" SONY CMOS image sensor, it delivers exceptional image quality with 4K resolution at 60fps. To ensure optimal framing, the DC-PTZ12-4K Series offers a range of optical zoom options including 3x, 10x, 12x, and 20x. This allows you to focus on specific individuals or objects, creating a more engaging and immersive experience.

For easy control and integration, the camera supports various communication protocols such as RS232, RS485, USB, and IR remote control. With its built-in electro mechanical PTZ system, the DC-PTZHD offers smooth and precise pan and tilt movements, making it ideal for a variety of applications including video conferencing, live streaming, and surveillance.

FEATURES:

- **1080P@60FPS Resolution:** Delivers high-quality images and smooth video playback.
- **4K Video Capture:** Offers exceptional detail and clarity for demanding applications.
- **3x/10x/12x/20x Optical Zoom:** Provides flexibility to focus on specific subjects or areas.
- **Remote Control:** Can be controlled using RS232, RS485, USB ports, or IR remote.
- **Electro Mechanical PTZ:** Offers precise and smooth pan and tilt movements.

4K PTZ Camera

SPECIFICATIONS:

Model	DC-PTZ12-4K
Sensor	1/2.8"SONY CMOS
Effective Pixels	8.29mega pixel
Video Signals	4K@30/25,1080p@60/50/30/25fps, 720p@60/50/30/25fps
Zoom	12x optical zoom
Lens	F=3.42-40.02mm
Aperture	F1.88-3.77
Horizontal Angle	80.56(W)-7.89°(T)
Vertical Angle	49.61°(W)-4.46°(T)
Diagonal Angle	89.51°(W)-9.04°(T)
Video Output	USB 3.0, HDMI
LAN	-
Network Protocol	-
Video Encoding Format	H.264, H.265, MJPG, YUY2
Video Resolution	4K(3840*2160)
Signal Standard	NTSC/PAL
Preset Position	User can set up to 255 presets (10 presets by IR remote)
Control Interface	RS-232 (input only), RS-485, USB
Shutter	1/30s-1/10000s, auto
Baud Rate	2400/4800/9600/38400bps
Control Protocol	VISCA, PELCO-D, PELCO-P(RS-232, RS-485)
USB Protocol	UVC1.1
Minimal Illumination	0.1Lux
SNR	≥50dB
Horizontal Rotation	350° (±175°) 0.1°/s ~ 100°/s
Vertical Rotation	180° (±90°)0.1°/s ~ 80°/s
Power Supply	DC 12V/2A
Power Consumption	12W
Work Temperature	0°C to 40°C
Product Size	247.1*152*169.6mm/285*217*197mm (Before/After Packing)
Product Weight	1.37kg/2.45kg (Net/Gross Weight)

Disclaimer: As per our company policy one of the constant product improvements the right is there for reserved to modify the product specification without prior notice and the picture shown in the datasheet is a design base, the actual picture may vary.